

View Online at <https://aerobasegroup.com/nsn/3415-01-382-0739>

Current Type:

Ac

Spindle Diameter:

0.750 inches

Furnished Items And Quantity:

Wheel, medium, 1; wheel, coarse, 1; adjustable tool rest, 2; heavy duty eyeshield, 2; water pot, 1; vented guard, 2

Horsepower Rating:

1.0

Power Source:

Electric motor

Mounting Type For Which Designed:

Pedestal

Spindle End Type:

Double

Spindle Speed In Rpm:

1725.0

Maximum Wheel Diameter Accommodated:

10.000 inches

Maximum Wheel Thickness Accommodated:

1.000 inches

Work Rest Design:

Plain

Criticality Code Justification:

Feat

Voltage In Volts:

115.0 and 220.0

Phase:

Single

Special Features:

6small diameter extended frame motors for work clearance; industrial quality totally enclosed motors rated for continuous use; balanced aluminous oxide vitrified wheels; lifetime sealed ball bearing construction; meets all osha standards; wire wheel available when specified upon ordering; shipping weight 143 pounds; height 50 in.; length 23 in.; grinder base 8 1/2 in. By 8 1/2 in.; pedestal base 18 in. By 18 in.; pedestal column 4 in. By 4 in.; pedestal construction heavy gauge welded steel

Frequency In Hertz:

60.0

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-a