Current Type:

Utility Grinding And Buffing Machine - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3415-01-382-0766

Ac
Spindle Diameter:
0.625 inches
Furnished Items And Quantity:
Wheel, medium, 1; wheel, coarse, 1; regular eyeshield, 2; water pot, 1; adjustable tool rest, 2; non vented guard, 2;
Horsepower Rating:
0.5
Power Source:
Electric motor
Mounting Type For Which Designed:
Pedestal
Spindle End Type:
Double
Spindle Speed In Rpm:
3450.0
Maximum Wheel Diameter Accommodated:
7.000 inches
Maximum Wheel Thickness Accommodated:
1.000 inches
Work Rest Design:
Plain
Criticality Code Justification:
Feat
Voltage In Volts:
115.0
Phase:
Single
Special Features:
Small diameter extended fram motors for work clearance; industrial quality totally enclosed motors rated for continuous use; balanced
aluminous oxide vitrified wheels; lifetime sealed ball bearing construction; meets all osha standards; wire wheel available when specified
upon ordering; shipping weight; 74 pounds; length 19 in.; height 43 3/4 in.; grinder base 8 1/2 in. By 6 in.; pedestal base 14 1/2 in. By 14
1/2 in.; pedestal column 4 in. By 4 in.; pedestal construction heavy gauge welded steel
Frequency In Hertz:
60.0
Quantity:
1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T284-2