

View Online at <https://aerobasegroup.com/nsn/3415-01-382-0799>

Current Type:

Ac

Spindle Diameter:

0.500 inches

Furnished Items And Quantity:

Multi-purpose tool rest, 2; adjustable eyeshield, 2; adjustable spark deflector, 2 wheel guard, 2; removable side plate, 2; water pot, 1 dust collection adapter, 2; wheel, coarse, 1; wheel, medium, 1; power cord, 1; plug, 1

Horsepower Rating:

0.3

Power Source:

Electric motor

Mounting Type For Which Designed:

Bench

Spindle End Type:

Double

Spindle Speed In Rpm:

3450.0

Maximum Wheel Diameter Accommodated:

6.000 inches

Maximum Wheel Thickness Accommodated:

0.750 inches

Work Rest Design:

Tilted

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Totally enclosed motor rated for continuous duty; lifetime, sealed, ball bearing construction; small diameter motor frame; meets all osha standards; height 12 1/4 in.; widthy 20 1/8 in.; front to back 9 5/16 in.; weight 29 pounds; single phase electricals will be supplied wired for 115 volt; wire wheel available when specified upon ordering

Frequency In Hertz:

60.0

Quantity:

1

Reference Number Differentiating Characteristics:

Feat

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-a