NSN 3415-01-382-0922

Utility Grinding And Buffing Machine - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3415-01-382-0922 **Current Type:** Ac **Spindle Diameter:** 0.500 inches **Furnished Items And Quantity:** Wheel, medium, 1; wheel, coarse, 1; regular eyeshield, 2; water pot, 1; adjustable tool rest, 2; nonvented guard, 2 **Horsepower Rating:** 0.3 **Power Source:** Electric motor **Mounting Type For Which Designed:** Pedestal Spindle End Type: Double Spindle Speed In Rpm: 3450.0 **Maximum Wheel Diameter Accommodated:** 6.000 inches **Maximum Wheel Thickness Accommodated:** 0.750 inches Work Rest Design: Plain **Criticality Code Justification:** Feat Voltage In Volts: 115.0 Phase: Single **Special Features:** Vsmall diameter extended frame motors for work clearance; industrial quality totally enclosed motors rated for continuous use; balanced aluminous oxide vitrified wheels; lifetime sealed ball bearing construction; meets all osha standards; grinder shipping weight 65 pounds; length 17 in.; height 43 1/2 in.; pedestal base 14 1/2 in. By 14 1/2 in.; pedestal column 4 in. By 4 in.; pedestal construction, heavy gauge welded steel; wire wheel available when specified when ordering Frequency In Hertz: 60.0 Quantity: Shelf Life: N/a **Unit Of Measure:**

Fiig: T204

No

Demilitarization: