

View Online at <https://aerobasegroup.com/nsn/3415-01-384-0064>

Current Type:

Ac

Spindle Diameter:

Between 0.500 inches and 0.875 inches

Furnished Items And Quantity:

10 in. Wheel, wet, 1; 5 in. Wheel, dry, 1; adjustable tool rest, 2; sliding angle jig, 1; eye shield, 1; wheel guard with removable side plate, 1

Current Rating In Amps:

2.0

Horsepower Rating:

0.2

Power Source:

Electric motor

Mounting Type For Which Designed:

Bench

Spindle End Type:

Double

Spindle Speed In Rpm:

Between 70.0 and 3450.0

Maximum Wheel Diameter Accommodated:

10.000 inches

Maximum Wheel Thickness Accommodated:

2.000 inches

Work Rest Design:

Plain

Voltage In Volts:

120.0

Phase:

Single

Special Features:

Industrial induction-type motor, shielded to keep out damaging dust; rocker-type switch for positive on-off control; slow speed 10 in. Wet wheel keeps hardened cutting tools cool to sharpen without damaging the tool's temper; 10 in. Wet wheel is aluminum oxide material; 5 in. Wheel is 0.625 in thickness; height 12 3/4 in.; width 12 in.; length 14 1/2 in.; weight 32 pounds

Frequency In Hertz:

60.0

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-a