

View Online at <https://aerobasegroup.com/nsn/3415-01-384-0064>

**Current Type:**

Ac

**Spindle Diameter:**

Between 0.500 inches and 0.875 inches

**Furnished Items And Quantity:**

10 in. Wheel, wet, 1; 5 in. Wheel, dry, 1; adjustable tool rest, 2; sliding angle jig, 1; eye shield, 1; wheel guard with removable side plate, 1

**Current Rating In Amps:**

2.0

**Horsepower Rating:**

0.2

**Power Source:**

Electric motor

**Mounting Type For Which Designed:**

Bench

**Spindle End Type:**

Double

**Spindle Speed In Rpm:**

Between 70.0 and 3450.0

**Maximum Wheel Diameter Accommodated:**

10.000 inches

**Maximum Wheel Thickness Accommodated:**

2.000 inches

**Work Rest Design:**

Plain

**Voltage In Volts:**

120.0

**Phase:**

Single

**Special Features:**

Industrial induction-type motor, shielded to keep out damaging dust; rocker-type switch for positive on-off control; slow speed 10 in. Wet wheel keeps hardened cutting tools cool to sharpen without damaging the tool's temper; 10 in. Wet wheel is aluminum oxide material; 5 in. Wheel is 0.625 in thickness; height 12 3/4 in.; width 12 in.; length 14 1/2 in.; weight 32 pounds

**Frequency In Hertz:**

60.0

**Quantity:**

1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T284-2