

View Online at <https://aerobasegroup.com/nsn/3415-01-384-0066>

Current Type:

Ac

Spindle Diameter:

0.625 inches

Furnished Items And Quantity:

Multi-purpose tool rest, 2; adjustable eyeshield, 2; adjustable spark deflector, 2; wheel guard, 2; removable side plate, 2; water pot, 1; dust collection adapter, 2; 24 volt push button station, magnetic starter, transformer and 3-leg overload protection, 1; wheel, coarse, 1; wheel, medium, 1

Horsepower Rating:

0.5

Power Source:

Electric motor

Mounting Type For Which Designed:

Pedestal

Spindle End Type:

Double

Spindle Speed In Rpm:

3450.0

Maximum Wheel Diameter Accommodated:

7.000 inches

Maximum Wheel Thickness Accommodated:

1.000 inches

Work Rest Design:

Tilted

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Totally enclosed motor rated for continuous duty; lifetime, sealed, ball bearing construction; small diameter motor frame; meets all osha standards; height 46 1/16 in.; width 23 3/8 in.; front to back 11 5/8 in.; weight 93 pounds; three phase electricals will be supplied wired for 230 volt, unless 460 volt is specified; wire wheel available when specified upon ordering

Frequency In Hertz:

60.0

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-a