

View Online at <https://aerobasegroup.com/nsn/3415-01-384-0066>

**Current Type:**

Ac

**Spindle Diameter:**

0.625 inches

**Furnished Items And Quantity:**

Multi-purpose tool rest, 2; adjustable eyeshield, 2; adjustable spark deflector, 2; wheel guard, 2; removable side plate, 2; water pot, 1; dust collection adapter, 2; 24 volt push button station, magnetic starter, transformer and 3-leg overload protection, 1; wheel, coarse, 1; wheel, medium, 1

**Horsepower Rating:**

0.5

**Power Source:**

Electric motor

**Mounting Type For Which Designed:**

Pedestal

**Spindle End Type:**

Double

**Spindle Speed In Rpm:**

3450.0

**Maximum Wheel Diameter Accommodated:**

7.000 inches

**Maximum Wheel Thickness Accommodated:**

1.000 inches

**Work Rest Design:**

Tilted

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

Totally enclosed motor rated for continuous duty; lifetime, sealed, ball bearing construction; small diameter motor frame; meets all osha standards; height 46 1/16 in.; width 23 3/8 in.; front to back 11 5/8 in.; weight 93 pounds; three phase electricals will be supplied wired for 230 volt, unless 460 volt is specified; wire wheel available when specified upon ordering

**Frequency In Hertz:**

60.0

**Quantity:**

1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T284-a