

View Online at <https://aerobasegroup.com/nsn/3416-00-003-4537>

Mounting Type:

Floor

Current Type:

Dc

Accessory Components And Quantity:

None specified

Design Type:

Saddle

Electric Motor Horsepower Rating:

30.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

3.500 inches

Maximum Chucking Distance Over Universal Carriage:

12.000 inches

Spindle Speed Quantity:

15

Spindle Speed Range In Rpm:

+41.0/+1507.0

Spindle Reversibility:

Reversible

Rated Swing:

15.000 inches

Actual Swing Over Bed:

17.375 inches

Swing Over Cross Slide:

11.625 inches

Maximum Distance From Spindle Nose To Turret Face:

44.000 inches

Universal Carriage Longitudinal Travel:

34.375 inches

Universal Carriage Cross Travel:

7.750 inches

Universal Carriage Feed Type:

Power

Longitudinal Feed Range Per Spindle Revolution:

+0.000 to 300.000 inches

Cross Feed Range Per Spindle Revolution:

+0.000 to 150.000 inches

Universal Carriage Compound:

Not included

Turret Carriage Longitudinal Travel:

36.125 inches

Turret Carriage Cross Travel:

11.000 inches

Turret Carriage Feed Type:

Power

Turret Carriage Longitudinal Feed Range Per Spindle Revolution:

+0.000 to 300.000

Turret Shape:

Pentagon

Turret Position Quantity:

5

Voltage In Volts:

430.0

Special Features:

4 axis numerical control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-a