

View Online at <https://aerobasegroup.com/nsn/3416-00-043-4210>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

30.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Design Type:

Screw

Electric Motor Horsepower Rating:

5.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+28.0 to 1800.0

Actual Swing Over Bed:

15.500 inches

Swing Over Cross Slide:

9.500 inches

Thread Change Quantity:

48

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

1.500 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand or power

Carriage Cross Feed Operation Method:

Hand or power

Gear Change Type:

Quick

Thread Quantity Range:

+4.0/+224.0 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Adqr, btyp, btsz, bttb, awlx, ashk, acdc, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b