

View Online at <https://aerobasegroup.com/nsn/3416-00-057-6960>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

20.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

Per mil-std 931

Design Type:

Screw

Electric Motor Horsepower Rating:

5.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Range In Rpm:

+8.0 to 4000.0

Rated Swing:

10.000 inches

Actual Swing Over Bed:

12.000 inches

Swing Over Cross Slide:

7.250 inches

Thread Change Quantity:

60

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

2 asa standard

Hole Diameter Through Spindle:

1.375 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

50

Gear Change Type:

Quick

Thread Quantity Range:

+3.0 to 184.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

2 type

Departure From Cited Document:

As modified by akyd

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b