

View Online at <https://aerobasegroup.com/nsn/3416-00-150-7111>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

36.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

3 jaw universal chuck 6 in.; 2 centers, solid, 60 degrees, no. 2 morse taper; 1 spindle sleeve bushing, no. 2 morse taper; 1 chuck, drill, no. 2 morse taper; 1 steady rest; 1 tool post

Design Type:

Screw

Electric Motor Horsepower Rating:

1.500

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+50.0 to 1350.0

Rated Swing:

Between 10.000 inches and 11.000 inches

Actual Swing Over Bed:

10.125 inches

Swing Over Cross Slide:

6.250 inches

Thread Change Quantity:

60

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

2 morse

Hole Diameter Through Spindle:

1.375 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

60

Gear Change Type:

Quick

Thread Quantity Range:

+4.0/+240.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Apgf, btwb, btzr, btsz, awlx, ashk, acdc, elec, freq, faaz, aaxx

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b