

View Online at <https://aerobasegroup.com/nsn/3416-00-163-9750>

**Mounting Type:**

Floor

**Current Type:**

Dc

**Accessory Components And Quantity:**

None specified

**Current Rating In Amps:**

Not rated

**Design Type:**

Saddle

**Electric Motor Horsepower Rating:**

30.000 or 60.000

**Power Source:**

Electric motor

**Maximum Bar Stock Diameter Accommodated:**

6.250 inches

**Maximum Chucking Distance Over Universal Carriage:**

21.000 inches

**Spindle Speed Quantity:**

32

**Spindle Speed Range In Rpm:**

+12.0 to 851.0

**Spindle Reversibility:**

Reversible

**Rated Swing:**

25.000 inches

**Actual Swing Over Bed:**

28.000 inches

**Swing Over Cross Slide:**

21.000 inches

**Maximum Distance From Spindle Nose To Turret Face:**

61.188 inches

**Universal Carriage Longitudinal Travel:**

47.062 inches

**Universal Carriage Cross Travel:**

13.750 inches

**Universal Carriage Feed Type:**

Power

**Longitudinal Feed Range Per Spindle Revolution:**

+0.050 to 25.000 inches

**Cross Feed Range Per Spindle Revolution:**

+0.050 to 25.000 inches

**Universal Carriage Compound:**

Not included

**Turret Carriage Longitudinal Travel:**

47.062 inches

**Turret Carriage Cross Travel:**

15.250 inches

**Turret Carriage Feed Type:**

Power

**Turret Carriage Longitudinal Feed Range Per Spindle Revolution:**

+0.050 to 25.000

**Turret Carriage Cross Feed Range Per Spindle Revolution:**

+0.050 to 25.000

**Turret Shape:**

Pentagon

**Turret Position Quantity:**

5

**Voltage In Volts:**

430.0

**Special Features:**

4 axis numerical control

**Reference Number Differentiating Characteristics:**

Elec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-a