

View Online at <https://aerobasegroup.com/nsn/3416-00-163-9750>

Mounting Type:

Floor

Current Type:

Dc

Accessory Components And Quantity:

None specified

Current Rating In Amps:

Not rated

Design Type:

Saddle

Electric Motor Horsepower Rating:

30.000 or 60.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

6.250 inches

Maximum Chucking Distance Over Universal Carriage:

21.000 inches

Spindle Speed Quantity:

32

Spindle Speed Range In Rpm:

+12.0 to 851.0

Spindle Reversibility:

Reversible

Rated Swing:

25.000 inches

Actual Swing Over Bed:

28.000 inches

Swing Over Cross Slide:

21.000 inches

Maximum Distance From Spindle Nose To Turret Face:

61.188 inches

Universal Carriage Longitudinal Travel:

47.062 inches

Universal Carriage Cross Travel:

13.750 inches

Universal Carriage Feed Type:

Power

Longitudinal Feed Range Per Spindle Revolution:

+0.050 to 25.000 inches

Cross Feed Range Per Spindle Revolution:

+0.050 to 25.000 inches

Universal Carriage Compound:

Not included

Turret Carriage Longitudinal Travel:

47.062 inches

Turret Carriage Cross Travel:

15.250 inches

Turret Carriage Feed Type:

Power

Turret Carriage Longitudinal Feed Range Per Spindle Revolution:

+0.050 to 25.000

Turret Carriage Cross Feed Range Per Spindle Revolution:

+0.050 to 25.000

Turret Shape:

Pentagon

Turret Position Quantity:

5

Voltage In Volts:

430.0

Special Features:

4 axis numerical control

Reference Number Differentiating Characteristics:

Elec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-a