

View Online at <https://aerobasegroup.com/nsn/3416-00-165-4201>

Mounting Type:

Bench

Current Type:

Ac

Center To Center Distance:

34.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

Lathe: qty: 1 hp motor wired to customers's voltage reqmts; electrics include an appropriate switching device. Q type 1 - bench cabinet, q type 1-thread dial indicator, q type 1- plain saddle stop, q type 1- large face plate, q type 1-steady rest, q type 2-dead centers 2mt, q type 1 -threading stop, q type 1-drive plate 5- -7/8" diameter, q type 1-4-way manual turret tool post, q type 1-micrometer carriage stop, q type 1-telescopic taper attachment, q type 1-spindle sleeve for 2mt center, q type 1-set of metric transposing gears, q type 1-tool kit, q type 1- instruction/maintenance manual

Design Type:

Screw

Operation Method:

Manual

Electric Motor Horsepower Rating:

0.500

Bed Type:

Permanent gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+52.0/+285.0

Rated Swing:

10.000 inches

Actual Swing Over Bed:

9.938 inches

Swing Over Cross Slide:

6.250 inches

Thread Change Quantity:

48

Headstock Drive Type:

Step cone pulley, back geared

Headstock Center Taper Size Designator:

2 morse

Hole Diameter Through Spindle:

0.844 inches

Carriage Quantity:

Carriage Longitudinal Feed Operation Method:

Power

Carriage Cross Feed Operation Method:

Power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+4.0/+224.0 per inch

Voltage In Volts:

230.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b