

View Online at <https://aerobasegroup.com/nsn/3416-00-165-4201>

**Mounting Type:**

Bench

**Current Type:**

Ac

**Center To Center Distance:**

34.000 inches

**Performance Type:**

Standard duty

**Purpose For Which Designed:**

General

**Accessory Components And Quantity:**

Lathe: qty: 1 hp motor wired to customers's voltage reqmts; electrics include an appropriate switching device. Q type 1 - bench cabinet, q type 1-thread dial indicator, q type 1- plain saddle stop, q type 1- large face plate, q type 1-steady rest, q type 2-dead centers 2mt, q type 1 -threading stop, q type 1-drive plate 5- -7/8" diameter, q type 1-4-way manual turret tool post, q type 1-micrometer carriage stop, q type 1-telescopic taper attachment, q type 1-spindle sleeve for 2mt center, q type 1-set of metric transposing gears, q type 1-tool kit, q type 1- instruction/maintenance manual

**Design Type:**

Screw

**Operation Method:**

Manual

**Electric Motor Horsepower Rating:**

0.500

**Bed Type:**

Permanent gap

**Electric Motor Quantity:**

1

**Spindle Speed Quantity:**

12

**Spindle Speed Range In Rpm:**

+52.0/+285.0

**Rated Swing:**

10.000 inches

**Actual Swing Over Bed:**

9.938 inches

**Swing Over Cross Slide:**

6.250 inches

**Thread Change Quantity:**

48

**Headstock Drive Type:**

Step cone pulley, back geared

**Headstock Center Taper Size Designator:**

2 morse

**Hole Diameter Through Spindle:**

0.844 inches

**Carriage Quantity:**

**Carriage Longitudinal Feed Operation Method:**

Power

**Carriage Cross Feed Operation Method:**

Power

**Carriage Feed Change Quantity:**

48

**Gear Change Type:**

Quick

**Thread Quantity Range:**

+4.0/+224.0 per inch

**Voltage In Volts:**

230.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-b