NSN 3416-00-186-4067

Engine Lathe - Page 1 of 2

Mounting Type:

Current Type:

Floor

Ac



View Online at https://aerobasegroup.com/nsn/3416-00-186-4067

Center To Center Distance:
42.000 inches
Performance Type:
Light duty
Purpose For Which Designed:
General
Design Type:
Screw
Electric Motor Horsepower Rating:
5.0
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Quantity:
12
Spindle Speed Range In Rpm:
+16.0 to 400.0
Rated Swing:
16.000 inches
Actual Swing Over Bed:
18.500 inches
Swing Over Cross Slide:
12.000 inches
Thread Change Quantity:
72
Headstock Drive Type:
Geared head
Headstock Center Taper Size Designator:
4 morse
Hole Diameter Through Spindle:
1.375 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:
Hand and power
Carriage Cross Feed Operation Method:
Hand and power

NSN 3416-00-186-4067 Engine Lathe - Page 2 of 2



Carriage Feed Change Quantity:
72
Gear Change Type:
Quick
Thread Quantity Range:
+1.0 to 224.0 per inch
Voltage In Volts:
220.0 and 440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T221-b