NSN 3416-00-186-4070

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-186-4070

Mounting Type:
Floor
Current Type:
Ac
Center To Center Distance:
48.000 inches
Performance Type:
Heavy duty
Purpose For Which Designed:
General
Accessory Components And Quantity:
None specified
Design Type:
Screw
Electric Motor Horsepower Rating:
10.0
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Quantity:
12
Spindle Speed Range In Rpm:
+14.0/+560.0
Rated Swing:
24.000 inches
Actual Swing Over Bed:
24.500 inches
Swing Over Cross Slide:
16.500 inches
Thread Change Quantity:
36
Headstock Drive Type:
Geared head
Headstock Center Taper Size Designator:
4 morse
Hole Diameter Through Spindle:
1.625 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:
Hand or power

NSN 3416-00-186-4070 Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:	
Hand or power	
Carriage Feed Change Quantity:	
36	
Gear Change Type:	
Quick	
Thread Quantity Range:	
+1.0 to 56.0 per inch	
Voltage In Volts:	
220.0	
Phase:	
Three	
Frequency In Hertz:	
60.0	
Reference Number Differentiating Characteristics:	
As differentiated by pacs adqr, btsz, bttb and pacs for electric motor data	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
Г221-b	