

View Online at <https://aerobasegroup.com/nsn/3416-00-186-4082>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Center To Center Distance:**

48.000 inches

**Performance Type:**

Standard duty

**Purpose For Which Designed:**

Toolroom

**Accessory Components And Quantity:**

Per mil-std 931

**Design Type:**

Screw

**Electric Motor Horsepower Rating:**

10.0

**Bed Type:**

Solid

**Electric Motor Quantity:**

1

**Spindle Speed Quantity:**

16

**Spindle Speed Range In Rpm:**

+10.0/+410.0

**Rated Swing:**

20.000 inches

**Actual Swing Over Bed:**

22.500 inches

**Swing Over Cross Slide:**

14.000 inches

**Thread Change Quantity:**

60

**Headstock Drive Type:**

Geared head

**Headstock Center Taper Size Designator:**

4 morse

**Hole Diameter Through Spindle:**

1.562 inches

**Carriage Quantity:**

1

**Carriage Longitudinal Feed Operation Method:**

Power or hand

**Carriage Cross Feed Operation Method:**

Hand or power

**Carriage Feed Change Quantity:**

60

**Gear Change Type:**

Quick

**Thread Quantity Range:**

+1.0/+60.0 per inch

**Voltage In Volts:**

220.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

Btzt, aksl, bttd, adqr, bttb, ashk, elec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-b