

View Online at <https://aerobasegroup.com/nsn/3416-00-186-4086>

Mounting Type:

Bench

Current Type:

Ac

Center To Center Distance:

20.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

0.50

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

6

Spindle Speed Range In Rpm:

+25.0/+500.0

Rated Swing:

10.000 inches

Actual Swing Over Bed:

10.125 inches

Swing Over Cross Slide:

5.875 inches

Thread Change Quantity:

48

Headstock Drive Type:

Step cone pulley, back geared

Headstock Center Taper Size Designator:

2 morse

Hole Diameter Through Spindle:

1.000 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand or power

Carriage Cross Feed Operation Method:

Hand or power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+4.0/+224.0 per inch

Voltage In Volts:

110.0

Phase:

Single

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by pacs bstst, bttb and pacs for electric motor data

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b