

View Online at <https://aerobasegroup.com/nsn/3416-00-186-4088>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

52.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

1.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+34.0/+875.0

Rated Swing:

13.000 inches

Actual Swing Over Bed:

13.125 inches

Swing Over Cross Slide:

8.120 inches

Thread Change Quantity:

48

Headstock Drive Type:

Step cone pulley, back geared

Headstock Center Taper Size Designator:

3 morse

Hole Diameter Through Spindle:

1.000 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+4.0/+224.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Btwb, btzr, btlw, bttb, btwb, awlx, ashk, acdc, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b