NSN 3416-00-189-7833

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-189-7833

Mounting Type:
Bench
Current Type:
Ac
Center To Center Distance:
26.000 inches
Performance Type:
Light duty
Purpose For Which Designed:
General
Accessory Components And Quantity:
None specified
Design Type:
Screw
Electric Motor Horsepower Rating:
0.750
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Quantity:
8
Spindle Speed Range In Rpm:
+34.0/+690.0
Rated Swing:
10.000 inches
Actual Swing Over Bed:
10.125 inches
Swing Over Cross Slide:
6.563 inches
Thread Change Quantity:
48
Headstock Drive Type:
Step cone pulley, back geared
Headstock Center Taper Size Designator:
2 morse
Hole Diameter Through Spindle:
1.375 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:

Hand and power

NSN 3416-00-189-7833 Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:
Hand and power
Carriage Feed Change Quantity:
48
Gear Change Type:
Quick
Thread Quantity Range:
+4.0/+224.0 per inch
Voltage In Volts:
110.0 and 220.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T221-h