## NSN 3416-00-235-0531

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-235-0531

Mounting Type:
Floor
Current Type:
Ac
Center To Center Distance:
33.000 inches
Performance Type:
Standard duty
Purpose For Which Designed:
Toolroom
Accessory Components And Quantity:
None specified
Design Type:
Screw
Electric Motor Horsepower Rating:
1.5
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Quantity:
8
Spindle Speed Range In Rpm:
+26.0/+885.0
Rated Swing:
16.000 inches
Actual Swing Over Bed:
16.250 inches
Swing Over Cross Slide:
9.625 inches
Thread Change Quantity:
48
Headstock Drive Type:
Step cone pulley, back geared
Headstock Center Taper Size Designator:
3 morse
Hole Diameter Through Spindle:
1.375 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:

Hand or power

## **NSN 3416-00-235-0531** Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:
Hand or power
Carriage Feed Change Quantity:
48
Gear Change Type:
Quick
Thread Quantity Range:
+4.0/+224.0 per inch
/oltage In Volts:
115.0 and 230.0
Phase:
Single
Frequency In Hertz:
60.0
Reference Number Differentiating Characteristics:
Btwb, btzr, btsz, bttb, awlx, ashk, acdc, elec, freq, faaz
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
Г221-b