Engine Lathe - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3416-00-235-0531



Mounting Type: Floor **Current Type:** Ac **Center To Center Distance:** 33.000 inches **Performance Type:** Standard duty **Purpose For Which Designed:** Toolroom Accessory Components And Quantity: None specified **Design Type:** Screw **Electric Motor Horsepower Rating:** 1.5 Bed Type: Solid **Electric Motor Quantity:** 1 **Spindle Speed Quantity:** 8 Spindle Speed Range In Rpm: +26.0/+885.0 **Rated Swing:** 16.000 inches **Actual Swing Over Bed:** 16.250 inches Swing Over Cross Slide: 9.625 inches **Thread Change Quantity:** 48 Headstock Drive Type: Step cone pulley, back geared Headstock Center Taper Size Designator: 3 morse Hole Diameter Through Spindle: 1.375 inches **Carriage Quantity:** 1 **Carriage Longitudinal Feed Operation Method:** Hand or power

# NSN 3416-00-235-0531

Engine Lathe - Page 2 of 2



**Carriage Cross Feed Operation Method:** 

Hand or power

## **Carriage Feed Change Quantity:**

48

Gear Change Type:

Quick

# Thread Quantity Range:

+4.0/+224.0 per inch

## Voltage In Volts:

115.0 and 230.0

Phase:

Single

Frequency In Hertz:

60.0

# **Reference Number Differentiating Characteristics:**

Btwb, btzr, btsz, bttb, awlx, ashk, acdc, elec, freq, faaz

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

T221-b