

View Online at <https://aerobasegroup.com/nsn/3416-00-235-0540>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

42.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

5.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

16

Spindle Speed Range In Rpm:

+12.0/+612.0

Rated Swing:

14.000 inches

Actual Swing Over Bed:

16.500 inches

Swing Over Cross Slide:

9.875 inches

Thread Change Quantity:

49

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

1.563 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand or power

Carriage Cross Feed Operation Method:

Hand or power

Carriage Feed Change Quantity:

49

Gear Change Type:

Quick

Thread Quantity Range:

+1.0/+60.0 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Btwb, adqr, btsz, bttb, byt, awlx, ashk, accd, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b