

View Online at <https://aerobasegroup.com/nsn/3416-00-235-0541>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

54.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

7.5

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+690.0/+2760.0

Rated Swing:

16.000 inches

Actual Swing Over Bed:

18.500 inches

Swing Over Cross Slide:

11.000 inches

Thread Change Quantity:

60

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

1.688 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand or power

Carriage Cross Feed Operation Method:

Hand or power

Carriage Feed Change Quantity:

60

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+120.0 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Adqr, awlx, ashk, acdc, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b