

View Online at <https://aerobasegroup.com/nsn/3416-00-242-2769>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

20.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

Per mil-std 931

Design Type:

Screw

Electric Motor Horsepower Rating:

3.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

6

Spindle Speed Range In Rpm:

+5.0/+3000.0

Rated Swing:

10.000 inches

Actual Swing Over Bed:

12.500 inches

Swing Over Cross Slide:

7.250 inches

Thread Change Quantity:

60

Headstock Drive Type:

Direct pulley, back geared

Headstock Center Taper Size Designator:

2 morse

Hole Diameter Through Spindle:

1.406 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

50

Gear Change Type:

Quick

Thread Quantity Range:

+3.0/+184.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Apgf, btwb, btzr, aksl, bttg, bttb, ashk, elec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b