

View Online at <https://aerobasegroup.com/nsn/3416-00-242-8148>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

36.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1 spindle faceplate, 9-1/2 in. Min dia; 1 steady rest, 1/4 in. To 3-1/2 in. Diameter capacity; 1 taper attachment

Design Type:

Screw

Electric Motor Horsepower Rating:

3.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+88.0/+3000.0

Rated Swing:

10.000 inches

Actual Swing Over Bed:

11.250 inches

Swing Over Cross Slide:

6.750 inches

Thread Change Quantity:

48

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

3 morse

Hole Diameter Through Spindle:

1.500 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+6.0/+368.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Btzt, awlx, ashk, accd, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b