

View Online at <https://aerobasegroup.com/nsn/3416-00-242-8824>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

72.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Design Type:

Screw

Electric Motor Horsepower Rating:

20.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

16

Spindle Speed Range In Rpm:

+18.0/+750.0

Rated Swing:

27.500 inches

Swing Over Cross Slide:

14.000 inches

Thread Change Quantity:

48

Headstock Drive Type:

Gearhead

Headstock Center Taper Size Designator:

5 morse

Hole Diameter Through Spindle:

2.188 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+0.750/+46.000 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As dif by bttd, adqr, bttb, ashk

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b