## NSN 3416-00-243-1412

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-243-1412

Mounting Type:
Floor
Current Type:
Ac
Center To Center Distance:
66.000 inches
Performance Type:
Light duty
Purpose For Which Designed:
Toolroom
Accessory Components And Quantity:
None specified
Design Type:
Screw
<b>Electric Motor Horsepower Rating:</b>
1.000
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Quantity:
8
Spindle Speed Range In Rpm:
+34.0/+875.0
Rated Swing:
13.000 inches
Actual Swing Over Bed:
13.125 inches
Swing Over Cross Slide:
8.125 inches
Thread Change Quantity:
48
Headstock Drive Type:
Step cone pulley, back geared
Headstock Center Taper Size Designator:
3 morse
Hole Diameter Through Spindle:
1.000 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:

Hand and power

## **NSN 3416-00-243-1412** Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:
Hand and power
Carriage Feed Change Quantity:
48
Gear Change Type:
Quick
Thread Quantity Range:
+4.0/+224.0 per inch
Voltage In Volts:
220.0 and 440.0
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
. <del>-</del>
Demilitarization:
No
Fiig:

T221-b