

View Online at <https://aerobasegroup.com/nsn/3416-00-250-6549>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

72.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

1 anti friction type taper attachment; 1 micrometer carriage stop

Design Type:

Plain

Electric Motor Horsepower Rating:

20.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

24

Spindle Speed Range In Rpm:

+23.0/+1500.0

Rated Swing:

20.000 inches

Actual Swing Over Bed:

20.000 inches

Swing Over Cross Slide:

13.000 inches

Headstock Drive Type:

Gearhead

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

1.563 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

66

Gear Change Type:

Quick

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

6as differentiated by purpose for which designed, rated swing, actual swing over bed, swing over cross slide, center to center distance, electric motor quantity, electric motor horsepower rating, current type, voltage in volts, frequency in hertz, and phase

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b