

View Online at <https://aerobasegroup.com/nsn/3416-00-260-0873>

Mounting Type:

Floor

Current Type:

Ac

Accessory Components And Quantity:

Per mil-std 931

Design Type:

Ram

Electric Motor Horsepower Rating:

5.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

1.000 inches

Maximum Chucking Distance Over Universal Carriage:

6.000 inches

Spindle Speed Quantity:

6

Spindle Speed Range In Rpm:

+67.0/+740.0

Spindle Reversibility:

Reversible

Actual Swing Over Bed:

14.000 inches

Swing Over Cross Slide:

6.000 inches

Maximum Distance From Spindle Nose To Turret Face:

18.750 inches

Universal Carriage Longitudinal Travel:

12.000 inches

Universal Carriage Cross Travel:

5.000 inches

Universal Carriage Feed Type:

Manual

Universal Carriage Compound:

Not included

Turret Carriage Longitudinal Travel:

6.000 inches

Turret Carriage Feed Type:

Manual or power

Turret Carriage Longitudinal Feed Range Per Spindle Revolution:

+0.003 to 0.030

Turret Shape:

Hexagon

Turret Position Quantity:

6

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Btsz, bttb, bttc, atjk, ashk, accdc, elec, amps, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-a