

View Online at <https://aerobasegroup.com/nsn/3416-00-333-5540>

**Mounting Type:**

Floor

**Center To Center Distance:**

77.000 inches

**Performance Type:**

Standard duty

**Purpose For Which Designed:**

General or toolroom

**Accessory Components And Quantity:**

Size too long taper key drive spindle nose in lieu of regular camlock spindle nose; 23/8-6 threaded spindle nose in lieu of regular camlock spindle nose; special paint colors; metric transposing gears; inch/metric crossfeed and compound rest dials; taper attachment; preparing lathe for coolant; cooling equipment; fine feed hand wheel; screw feed doubletool slide; hardened taper tailstock spindle; hardened and ground cross feed and compound rest screws

**Design Type:**

Screw

**Bed Type:**

Permanent gap

**Spindle Speed Quantity:**

8 or 16

**Spindle Speed Range In Rpm:**

+15.0/+980.0

**Rated Swing:**

Between 16.000 inches and 24.000 inches

**Actual Swing Over Bed:**

25.125 inches

**Swing Over Cross Slide:**

18.750 inches

**Thread Change Quantity:**

48

**Headstock Drive Type:**

Direct pulley, back geared or step cone pulley

**Headstock Center Taper Size Designator:**

3 morse

**Carriage Quantity:**

1

**Carriage Longitudinal Feed Operation Method:**

Hand and power

**Carriage Cross Feed Operation Method:**

Hand and power

**Gear Change Type:**

Plain or quick

**Thread Quantity Range:**

+4.0/+224.0 per inch

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-b