

View Online at <https://aerobasegroup.com/nsn/3416-00-449-4068>

Mounting Type:

Bench

Current Type:

Ac

Center To Center Distance:

18.000 inches

Performance Type:

Light duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

Per mil-std 931

Design Type:

Screw

Electric Motor Horsepower Rating:

0.75

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+25.0/+1500.0

Rated Swing:

8.000 inches

Actual Swing Over Bed:

8.500 inches

Swing Over Cross Slide:

2.625 inches

Thread Change Quantity:

33

Headstock Drive Type:

Step cone pulley, back geared

Headstock Center Taper Size Designator:

2 morse

Hole Diameter Through Spindle:

1.125 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

33

Gear Change Type:

Quick

Thread Quantity Range:

+10.0/+144.0 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Ashk, acdcd, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T221-b