

View Online at <https://aerobasegroup.com/nsn/3416-00-449-7188>

Mounting Type:

Bench

Current Type:

Ac

Center To Center Distance:

35.000 inches

Accessory Components And Quantity:

4 belts/v/; 1 bushing, spindle ctr.; 2 ctrs., tailstock, headstock, no.2 morse taper; 1 chuck, lathe, ind., med.Duty, 4 jaw, 10 in.W/wrench; 1 chuck, lathe, scroll self ctr., med.Duty, 3 jaw, univ., w/rev.Jaws, 6 in.W/wrench; 24 cutter bit, tool holder h-speed steel, unfinished, sq, 5/16by2-3/4 in.; 1 cutter bit, tool holder, unfinished, beveled, 1/8by3/4by6 in.; 3 cutter bit, tool holder, unfinished, sq, 1/4by2-1/8 in.; 1 dial, indicating, thd chasing; 1 dog set, 1 ea, bent tail, single screw 1/2, 3/4, 1, 1-1/4, 1-1/2 in.Cap; 1 holder, cutting tool, boring w/boring bar, 30, 45 and 90 degrees end caps, cutter bits and wrench, 1/2by1-1/8 in.Shank, 3/4 in.Bar dia; 1 holder, cutting off, straight shank, w/cutter bit, and wrench, 1/2by1-1/8 in.Shank; 1 ea rh, lh, straight holder, cutting tool, turning, offset, w/cutter bit and wrench, 1/2by1-1/8 in.Shank; 1 ea wrench, tailstock, tool post

Electric Motor Horsepower Rating:

0.750

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

8

Rated Swing:

12.000 inches

Actual Swing Over Bed:

12.500 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

2 morse

Hole Diameter Through Spindle:

1.313 inches

Carriage Quantity:

1

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

57

Gear Change Type:

Quick

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b