NSN 3416-00-449-7192

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-449-7192

Mounting Type:
Floor
Current Type:
Ac
Center To Center Distance:
48.000 inches
Performance Type:
Heavy duty
Purpose For Which Designed:
General
Accessory Components And Quantity:
Per mil-std 931
Design Type:
Screw
Electric Motor Horsepower Rating:
20.0
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Quantity:
16
Spindle Speed Range In Rpm:
+11.0/+500.0
Rated Swing:
20.000 inches
Actual Swing Over Bed:
22.500 inches
Swing Over Cross Slide:
13.000 inches
Thread Change Quantity:
48
Headstock Drive Type:
Geared head
Headstock Center Taper Size Designator:
5 morse
Hole Diameter Through Spindle:
2.188 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:

Hand and power

NSN 3416-00-449-7192 Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:
Hand and power
Carriage Feed Change Quantity:
48
Gear Change Type:
Quick
Thread Quantity Range:
+1.0/+46.0 per inch
/oltage In Volts:
220.0 and 440.0
Phase:
Гhree
Frequency In Hertz:
60.0
Reference Number Differentiating Characteristics:
Bttfj, adqr, ashk, elec
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
Г221-b