

View Online at <https://aerobasegroup.com/nsn/3416-00-460-1550>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

48.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

Per mil-std 931

Design Type:

Screw

Electric Motor Horsepower Rating:

20.000

Bed Type:

Removable block gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

24

Spindle Speed Range In Rpm:

+6.0/+338.0

Swing Over Cross Slide:

20.000 inches

Thread Change Quantity:

55

Actual Swing Through Open Gap:

40.000 inches

Rated Swing Over Closed Gap:

26.000 inches

Actual Swing Over Closed Gap:

26.500 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

5 morse

Hollow Spindle Hole Size:

11.500 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

55

Gear Change Type:

Quick

Thread Quantity Range:

+1.0/+64.0 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Awha, adqr, btyn, ashk

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b