

View Online at <https://aerobasegroup.com/nsn/3416-00-460-1550>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Center To Center Distance:**

48.000 inches

**Performance Type:**

Heavy duty

**Purpose For Which Designed:**

General

**Accessory Components And Quantity:**

Per mil-std 931

**Design Type:**

Screw

**Electric Motor Horsepower Rating:**

20.000

**Bed Type:**

Removable block gap

**Electric Motor Quantity:**

1

**Spindle Speed Quantity:**

24

**Spindle Speed Range In Rpm:**

+6.0/+338.0

**Swing Over Cross Slide:**

20.000 inches

**Thread Change Quantity:**

55

**Actual Swing Through Open Gap:**

40.000 inches

**Rated Swing Over Closed Gap:**

26.000 inches

**Actual Swing Over Closed Gap:**

26.500 inches

**Headstock Drive Type:**

Geared head

**Headstock Center Taper Size Designator:**

5 morse

**Hollow Spindle Hole Size:**

11.500 inches

**Carriage Quantity:**

1

**Carriage Longitudinal Feed Operation Method:**

Hand and power

**Carriage Cross Feed Operation Method:**

Hand and power

**Carriage Feed Change Quantity:**

55

**Gear Change Type:**

Quick

**Thread Quantity Range:**

+1.0/+64.0 per inch

**Voltage In Volts:**

220.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

Awha, adqr, btyn, ashk

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T221-b