

View Online at <https://aerobasegroup.com/nsn/3416-00-517-1051>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

30.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

1 belt set, complete; 1 center, half; 1 center, headstock; 1 center, tailstock; chuck, drill, 1/2 in. Capacity; 1 chuck, spindle nose, lathe; 1 chuck, 3 jaw, universal, 6 in.; 1 chuck, 4 jaw, independent 8 in.; 1 collect set, 1/16 in. To 1-3/8 in. Range, 11 collects; 1 coolant system, motor driven; 1 dog set, bent, 1 in., 2 in., 3 in., 4 in. Sizes; 1 holder, tool, knurling armstrong no. 1k; 1 holder, tool, boring armstrong no. 9; 1 holder, tool, cut-off armstrong no. 31-l; 1 holder, tool, cut-off armstrong no. 31-r; 1 holder, tool, turning armstrong no. 1r; 1 holder, tool, turning armstrong no. 1-l; 1 mandrel set, lathe; 1 motor, 5 hp, 220/440v, 60 cycles, 3 phase, 1800 rpm; 1 rest, follow; 1 starter, non-reversing, magnetic; 1 switch, push, remoe control; 1 taper attachment, telescopic

Design Type:

Screw

Electric Motor Horsepower Rating:

5.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

16

Spindle Speed Range In Rpm:

+28.0/+1000.0

Rated Swing:

14.000 inches

Actual Swing Over Bed:

14.000 inches

Swing Over Cross Slide:

9.000 inches

Thread Change Quantity:

48

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

3 asa standard

Hole Diameter Through Spindle:

1.406 inches

Carriage Quantity:

1

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+4.0/+80.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

2 type and 14 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b