

View Online at <https://aerobasegroup.com/nsn/3416-00-528-1924>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

60.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

Per mil-std 931

Design Type:

Screw

Electric Motor Horsepower Rating:

60.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

36

Spindle Speed Range In Rpm:

+6.0/+600.0

Rated Swing:

40.000 inches

Actual Swing Over Bed:

40.000 inches

Swing Over Cross Slide:

25.000 inches

Thread Change Quantity:

48

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

6 morse

Hole Diameter Through Spindle:

3.000 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+2.0/+28.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

4025 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T221-b