

View Online at <https://aerobasegroup.com/nsn/3416-00-528-7903>

Mounting Type:

Floor

Current Type:

Ac

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

25.0

Bed Type:

Sliding gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

16

Spindle Speed Range In Rpm:

+3.25/+400.00

Swing Over Cross Slide:

19.500 inches

Thread Change Quantity:

48

Actual Swing Through Open Gap:

56.000 inches

Actual Swing Over Closed Gap:

30.500 inches

Distance Between Open Centers:

156.000 inches

Distance Between Closed Centers:

96.000 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

6 morse

Hole Diameter Through Spindle:

2.250 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+0.750/+46.000 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Btwj, btk

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

T221-b