NSN 3416-00-528-7903

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-528-7903

Mounting Type:
Floor
Current Type:
Ac
Performance Type:
Heavy duty
Purpose For Which Designed:
General
Accessory Components And Quantity:
None specified
Design Type:
Screw
Electric Motor Horsepower Rating:
25.0
Bed Type:
Sliding gap
Electric Motor Quantity:
1
Spindle Speed Quantity:
16
Spindle Speed Range In Rpm:
+3.25/+400.00
Swing Over Cross Slide:
19.500 inches
Thread Change Quantity:
48
Actual Swing Through Open Gap:
56.000 inches
Actual Swing Over Closed Gap:
30.500 inches
Distance Between Open Centers:
156.000 inches
Distance Between Closed Centers:
96.000 inches
Headstock Drive Type:
Geared head
Headstock Center Taper Size Designator:
6 morse
Hole Diameter Through Spindle:
2.250 inches
Carriage Quantity:

NSN 3416-00-528-7903 Engine Lathe - Page 2 of 2



Carriage Longitudinal Feed Operation Method:
Hand and power
Carriage Cross Feed Operation Method:
Hand and power
Carriage Feed Change Quantity:
48
Gear Change Type:
Quick
Thread Quantity Range:
+0.750/+46.000 per inch
Voltage In Volts:
220.0 and 440.0
Phase:
Three
Frequency In Hertz:
60.0
Reference Number Differentiating Characteristics:
Btwj, btwk
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T221-b