

View Online at <https://aerobasegroup.com/nsn/3416-00-528-8417>

Mounting Type:

Floor

Current Type:

Ac

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

5.000

Bed Type:

Sliding gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

24

Spindle Speed Range In Rpm:

+24.0/+700.0

Swing Over Cross Slide:

13.000 inches

Thread Change Quantity:

24

Rated Swing Through Open Gap:

38.000 inches

Actual Swing Through Open Gap:

40.500 inches

Rated Swing Over Closed Gap:

16.000 inches

Actual Swing Over Closed Gap:

20.500 inches

Distance Between Open Centers:

120.000 inches

Distance Between Closed Centers:

168.000 inches

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

1.375 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand or power

Carriage Cross Feed Operation Method:

Hand or power

Carriage Feed Change Quantity:

24

Gear Change Type:

Quick

Thread Quantity Range:

+1.0/+120.0 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-b