

View Online at <https://aerobasegroup.com/nsn/3416-00-720-2786>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

54.000 inches

Performance Type:

Heavy duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

15.0

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Quantity:

32

Spindle Speed Range In Rpm:

+6.0/+600.0

Rated Swing:

16.000 inches

Actual Swing Over Bed:

21.500 inches

Swing Over Cross Slide:

10.500 inches

Thread Change Quantity:

60

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

4 morse

Hole Diameter Through Spindle:

2.063 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand or power

Carriage Cross Feed Operation Method:

Hand or power

Carriage Feed Change Quantity:

60

Gear Change Type:

Quick

Thread Quantity Range:

+1.5/+92.0 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by center to center distance, spindle speed range in rpm, electric motor quantity, horsepower rating, current type, voltage in volts, frequency in hertz and phase

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-b