## NSN 3416-00-753-9416

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-753-9416 **Mounting Type:** Floor **Current Type:** Ac **Center To Center Distance:** 48.000 inches **Performance Type:** Heavy duty **Purpose For Which Designed:** General **Accessory Components And Quantity:** Per mil-std 931 **Design Type:** Screw **Electric Motor Horsepower Rating:** 20.000 **Bed Type:** Solid **Electric Motor Quantity: Spindle Speed Quantity:** 12 Spindle Speed Range In Rpm: +7.0/+270.0 **Rated Swing:** 25.000 inches **Actual Swing Over Bed:** 27.500 inches **Swing Over Cross Slide:** 18.250 inches **Thread Change Quantity: Headstock Drive Type:** Geared head **Headstock Center Taper Size Designator:** 

5 morse

**Hollow Spindle Hole Size:** 

9.000 inches

**Carriage Quantity:** 

**Carriage Longitudinal Feed Operation Method:** 

Power

## **NSN 3416-00-753-9416** Engine Lathe - Page 2 of 2



Carriage Cross Feed Operation Method:
Power
Carriage Feed Change Quantity:
54
Gear Change Type:
Quick
Thread Quantity Range:
+1.250/+72.000 per inch
Voltage In Volts:
230.0 and 460.0
Phase:
Three
Frequency In Hertz:
60.0
Reference Number Differentiating Characteristics:
Bttb, awlx, ashk, acdc, elec, freq, faaz
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
Г221-b