

View Online at <https://aerobasegroup.com/nsn/3416-00-761-5332>

Mounting Type:

Floor

Current Type:

Ac

Accessory Components And Quantity:

As per mil-std 931

Design Type:

Ram

Electric Motor Horsepower Rating:

5.000 or 10.000

Power Source:

Electric motor

Maximum Bar Stock Diameter Accommodated:

1.500 inches

Maximum Chucking Distance Over Universal Carriage:

10.000 inches

Spindle Speed Quantity:

16

Spindle Speed Range In Rpm:

+45.0/+2262.0

Spindle Reversibility:

Reversible

Actual Swing Over Bed:

15.375 inches

Swing Over Cross Slide:

7.000 inches

Maximum Distance From Spindle Nose To Turret Face:

26.750 inches

Universal Carriage Longitudinal Travel:

17.250 inches

Universal Carriage Cross Travel:

8.000 inches

Universal Carriage Feed Type:

Power and manual

Longitudinal Feed Range Per Spindle Revolution:

+0.003 to 0.030 inches

Cross Feed Range Per Spindle Revolution:

+0.0025 to 0.0260 inches

Universal Carriage Compound:

Not included

Turret Carriage Longitudinal Travel:

10.000 inches

Turret Carriage Feed Type:

Power and manual

Turret Carriage Longitudinal Feed Range Per Spindle Revolution:

+0.003 to 0.030

Turret Shape:

Hexagon

Turret Position Quantity:

6

Voltage In Volts:

220.0

Phase:

Three

Special Features:

Automatic electro-cycle

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by spindle speed qty, spindle speed range in rpm, spindle reversibility, power source, electric motor horsepower rating, current type, voltage in volts, current rating in amperes, freq in hertz, phase, and special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-a