

View Online at <https://aerobasegroup.com/nsn/3416-00-840-9717>

General Description:

3.94 in. Min swing over bed, 12 in. Min bed lg, 3.25 in. Min distance between centers, sealed bearing mtd spindle w/ww style collet accommodation, plain pushtype tailstock w/ww style collet accommodation, 3/16-wwmax collet capacity, additional equipment as follows, 1. Belt, round, 3 ft lg, 2 each. 2. Chuck, drill, 0-1/4in. Capacity w/arbor, 1 each. 3. Chuck, 3 jaw w/reversable jaws, 1 each. 4. Chuck, wheel, 0.221 to 0.523in. Capacity, 1 each. 5. Collet set, ww style, c/o 1each of the following sizes, no. 5, 6, 7, 8, 9, 10, 12, 15, 16, 20, 24, 25, 28, 30, 32, 35, 40, 43, 45, 47, 50, 55, 60, 63, 70, 80. 6. Drive motor for open headstock, 8 spindle speeds, 3000 maximum rpm, w/electromagnetic interference control, 1 each. 7. Slide rest, 3 slided w/toolpost, 1 each. 8. Tool set, c/o the following components, square cutters, 6 each, round cutters, 2 each, round toolholder, 1 each. 9. Screw cutting attachment, right and left hand inch threads.

Specification Or Standard:

I type

Departure From Cited Designator:

As modified by the additional equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23900