

View Online at <https://aerobasegroup.com/nsn/3416-00-932-4356>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

18.000 inches

Performance Type:

Standard duty

Purpose For Which Designed:

Toolroom

Accessory Components And Quantity:

Per mil-std 931

Design Type:

Screw

Electric Motor Horsepower Rating:

1.000

Bed Type:

Solid

Electric Motor Quantity:

1

Spindle Speed Range In Rpm:

+125.0/+3000.0

Actual Swing Over Bed:

11.000 inches

Swing Over Cross Slide:

6.000 inches

Thread Change Quantity:

27

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

5c harding

Hole Diameter Through Spindle:

1.250 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand and power

Carriage Cross Feed Operation Method:

Hand and power

Gear Change Type:

Quick

Thread Quantity Range:

+11.0/+108.0 per inch

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Awlx, ashk, acdc, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T221-b