NSN 3416-00-979-1349

Engine Lathe - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3416-00-979-1349

Mounting Type:
Floor
Current Type:
Ac
Center To Center Distance:
17.000 inches
Performance Type:
Light duty
Purpose For Which Designed:
General
Accessory Components And Quantity:
Per mil-std 931
Design Type:
Plain
Electric Motor Horsepower Rating:
1.000
Bed Type:
Solid
Electric Motor Quantity:
1
Spindle Speed Range In Rpm:
+230.0/+3500.0
Actual Swing Over Bed:
9.000 inches
Swing Over Cross Slide:
5.750 inches
Headstock Center Taper Size Designator:
50 harding
Hole Diameter Through Spindle:
1.062 inches
Carriage Quantity:
1
Carriage Longitudinal Feed Operation Method:
Hand
Carriage Cross Feed Operation Method:
Hand
Gear Change Type:
Quick
Voltage In Volts:
220.0
Phase:
Three

NSN 3416-00-979-1349

Engine Lathe - Page 2 of 2



Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

Awlx, ashk, acdc, elec, freq, faaz

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

T221-b