

View Online at <https://aerobasegroup.com/nsn/3416-00-998-8921>

Mounting Type:

Floor

Current Type:

Ac

Performance Type:

Heavy duty

Purpose For Which Designed:

General

Accessory Components And Quantity:

None specified

Design Type:

Screw

Electric Motor Horsepower Rating:

40.0

Bed Type:

Sliding gap

Electric Motor Quantity:

1

Spindle Speed Quantity:

36

Spindle Speed Range In Rpm:

+6.0/+600.0

Swing Over Cross Slide:

25.000 inches

Thread Change Quantity:

48

Rated Swing Through Open Gap:

65.000 inches

Actual Swing Through Open Gap:

65.000 inches

Rated Swing Over Closed Gap:

40.000 inches

Actual Swing Over Closed Gap:

39.000 inches

Err Default:

Err default

Err Default:

Err default

Headstock Drive Type:

Geared head

Headstock Center Taper Size Designator:

6 asa standard

Hole Diameter Through Spindle:

3.063 inches

Carriage Quantity:

1

Carriage Longitudinal Feed Operation Method:

Hand or power

Carriage Cross Feed Operation Method:

Hand or power

Carriage Feed Change Quantity:

48

Gear Change Type:

Quick

Thread Quantity Range:

+0.750/+46.000 per inch

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-b